

SEPARATOR FOR BATTERY AND ALKALINE SECONDARY BATTERY USING THIS SEPARATOR

SEPARATOR FOR BATTERY AND ALKALINE SECONDARY BATTERY USING THIS SEPARATOR

Patent Number: JP9330694
Publication date: 1997-12-22
Inventor(s): SAKAI TETSUO; UEHARA HITOSHI; NISHIDA MASAOKI; YAMASHITA HIROYUKI; TAMURA KOICHI
Applicant(s): AGENCY OF IND SCIENCE & TECHNOL; KANAI JUYO KOGYO CO LTD
Requested Patent: ☐ JP9330694
Application Number: JP19970058177 19970312
Priority Number(s):
IPC Classification: H01M2/16 ; H01M2/18 ; H01M10/24
EC Classification:
EC Classification:
Equivalents:

Abstract

PROBLEM TO BE SOLVED: To eliminate coming off of ion exchange fine particles, make a separator excellent in an electrolyte holding property so that ion exchange performance can be displayed over a long period, by using a binder resin sealed to be infiltrated in a fine void or fine groove formed in a surface part of organic fiber constituting a porous sheet, and securing the ion exchange fine particles.

SOLUTION: In a surface part of an olefin fiber 1, a fine void 2 or fine groove is provided. The fine void 2 or fine groove is formed by etching the olefin fiber 1 with an organic solvent. In a manner partly infiltrating in this fine void 2 or fine groove, a binder resin 3 is secured in a structure protruding to the outside, in a tip end part of this protruding part, an ion exchange fine particle 4 is fixed. As the binder resin 3, a styrene-ethylene-butylene-styrene(SEBS) thermoplastic copolymer is desirable.

Data supplied from the esp@cenet database - I2

SEPARATOR FOR ALKALINE SECONDARY BATTERY